


# CERTIFICATE OF CONFORMANCE

SUPPLIED TO : M/S Safetrack Engineers Pvt.Ltd., Noida.  
ARTICLE NAME : BRAZING FLUX SILVER POWDER  
ARTICLE CODE : LOMELT  
SHELF LIFE : 6 MONTH  
QUANTITY : 2.000 Kgs.

INVOICE NO. / CAT-017  
TRANSFER INV. NO. / CT-017  
A-11, 1st Floor, Sector-9 Noida-201301 (U.P.)  
Mobile: +91-9971458222 | Telefax: +91-120-4156920  
Web: www.safetrackengineers.in | E-mail: safetrackengineers@gmail.com  
DATE: 28-02-2015  
BATCH NO. 2702SF

PROPERTIES	SPECIFICATION	FINDING
p H PHYSICAL STATE COLOUR CONTAINTS MOISTURE % CHLORINE ACTIVITY RANGE	7-9 POWDER WHITE POTASSIUM SALTS <2% NIL 550oC - 800oC	8.6 POWDER WHITE POTASSIUM SALTS <2% NIL APPROX 550oC-750oC
		

SAFETRACK ENGINEERS PVT. LTD.  
A-11, 1st Floor, Sector-9 Noida-201301 (U.P.)  
Mobile: +91-9971458222 | Telefax: +91-120-4156920  
Web: www.safetrackengineers.in | E-mail: safetrackengineers@gmail.com

R 134a COMPATIBLE  
AFTER MELTING GIVES CLEAR & VISCOUS LIQUID  
EASILY REMOVABLE WATER SOLUBLE RESIDUE

### DIRECTION : BEFORE USE :

REMOVE OIL, GREASE OR OTHER CONTAMINATS FROM THE SURFACE TO BE BRAZED.  
CHECK p H IN CASE OF OVER SHELF LIFE.

### AFTER USE :

CLEAN FLUX RESIDUE FROM BRAZED JOINT USING HOT WATER (60°c ) FOR BEST RESULT  
IF UNAVAILABLE, ROOM TEMPRATURE WATER MAY ALSO BE USED.

REMAINING FLUX TO BE KEPT IN CLOSED CONTAINER.  
ALTHOUGH FLUXES ARE MILDER TO HUMAN HYGIENIC CARE IS RECOMMENDED.

**SAFETRACK ENGINEERS PVT. LTD.**  
A-11, 1st Floor, Sector-9 Noida- 201301 (U.P.)  
Mobile: +91-9971458222 | Telefax: +91-120-4156920  
Web: www.safetrackengineers.in | E-mail: safetrackengineers@gmail.com